

MATERIAL SAFETY DATA SHEET

SB-442 GENERAL STAIN REMOVER

Page Number: 1/3

Revision Date: 06/25/10

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

Product Name: SB-442 GENERAL STAIN REMOVER

Company Name: SUREBOND

2801 International Lane Madison, WI 53704 Phone: (608) 237-7554

FOR CHEMICAL EMERGENCY CALL (800) 535-5053

PRODUCT TYPE: ALKALINE LIQUID HARD SURFACE CLEANER

CHEMICAL FORMULA: MIXTURE CHEMICAL NAME: N/A

SECTION 2 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE:

Eyes: Will cause severe persistent irritation.

Skin: Will cause moderate irritation.

Inhalation: Spray mist or fog may cause irritation to nose, throat and lungs.

Ingestion: May cause corrosive damage to mouth, throat or stomach. Large oral doses may cause diarrhea,

intestinal bleeding.

HAZARD RATINGS (0-4): Flammability: 0 Health: 1 Personal Protection: B Physical Hazard: 0

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	UAS		ILV	ILV
COMPONENT	REG#	<u>%</u>	<u>osha</u>	<u>ACGIH</u>
Sodium Metalsilicate	6834-92-0	3 - 5	N/A	N/A
Nonylphenol Ethoxylate	9016-45-9	1 - 2	N/A	N/A
Ethylene Glycol Monobutyl Ether*	111-76-2	3 - 6	25 ppm skin	25 ppm skin

^{*}This item is subject to reporting requirements under SARA III, Section 313.

SECTION 4 - PHYSICAL PROPERTIES

APPEARANCE: Clear, colorless liquid with mild odor

pH: 13 +/- 0.3 VISCOSITY: 5.0 cps

FREEZING POINT: 32° F, water, F/T stable

BOILING POINT: 212° F, water

VAPOR PRESSURE: <18
VAPOR DENSITY: <1
SOLUBILITY IN WATER: Complete



MATERIAL SAFETY DATA SHEET

SB-442 GENERAL STAIN REMOVER

Page Number: 2/3

Revision Date: 06/25/10

 VOLATILE (% WT):
 90 - 95

 SPECIFIC GRAVITY:
 1.04

 EVAPORATION RATE:
 <1</td>

 VOC:
 <50 g/l</td>

SECTION 5 - FIRE AND EXPLOSION HAZARD

FLASH POINT: None, water solution

LOWER EXPLOSION LIMIT: N/A UPPER EXPLOSION LIMIT: N/A

AUTO IGNITION TEMP: N/A EXTINGUISHING MEDIUM: N/A SPECIAL FIRE FIGHTING PROCEDURES:

Cool and use caution when approaching fire-exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers may burst in heat of fire.

SECTION 6 - HEALTH HAZARDS

THRESHOLD LIMIT VALUES: None established. PRIMARY ROUTES OF EXPOSURE: Eye, skin

CARCINOGENS OR SUSPECTED CARCINOGENIC INGREDIENTS: None

SECTION 7 - EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush thoroughly with water for <u>at least 15 minutes</u>. Hold eyelids apart to ensure flushing of

entire eye surface. If irritation persists, seek medical attention.

IF ON SKIN: Flush thoroughly with water. Wash clothing before reuse.

IF INHALED: Remove subject to fresh air. If distress persists, contact a physician.

IF SWALLOWED: Wash mouth with water. Give large amounts of water or milk to drink. Call a physician. Never

give anything by mouth to an unconscious person.

SECTION 8 - REACTIVITY

STABILITY: Stable CONDITIONS TO AVOID: None known

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid strong acids (e.g. muriatic acid).

SECTION 9 - SPILLS OR LEAK PROCEDURE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

For small spills that can be handled routinely, mop up as much as possible, then flush residue into sanitary sewer system.

For large spills, collect with suitable absorbent, sweep up and place bulk material in container for disposal under current Local, State and Federal regulations.



MATERIAL SAFETY DATA SHEET

SB-442 GENERAL STAIN REMOVER

Page Number: 3/3

Revision Date: 06/25/10

WASTE DISPOSAL METHODS:

Waste from normal product use can be flushed to sanitary sewer which leads to sewage treatment facility. Undiluted, this product is regulated by RCRA for disposal as a corrosive waste. Regulated quantities should be disposed of by neutralization at a permitted facility in accordance with Local, State and Federal regulations.

SECTION 10 - SPECIAL PROTECTION

VENTILATION TYPE: General room ventilation in normally adequate. Substantial misting can be

controlled with local exhaust.

RESPIRATORY PROTECTION: None needed under normal use conditions. If mists are not controlled by local

exhaust, use NIOSH approved respiratory equipment.

PROTECTIVE GLOVES: Impervious.

EYE PROTECTION: Safety glasses is splashing is likely.

OTHER PROTECTIVE EQUIPMENT: Use good personal hygiene practices. Eye wash, safety shower.

SECTION 11 - STORAGE AND HANDLING

Keep from freezing. Store at 50° - 120°F.

Protect food products and packaging before using this product.

SECTION 12 - SHIPPING

PROPER SHIPPING NAME: Compounds, Cleaning Liquid (Contains Sodium Hydroxide)

U.S. DOT HAZARD CLASS: 8, NA 1760, PG III

LABEL REQUIREMENTS: Corrosive

For gallons in 4 x 1 carton:

PROPER SHIPPING NAME: Consumer Commodity, ORM-D

U.S. DOT HAZARD CLASS:

LABEL REQUIREMENTS: Consumer Commodity, ORM-D

SECTION 13 - MISCELLANEOUS

ABBREVIATIONS:

N/A: Not applicable UNK: Unknown N/D: Not determined < : Less than

> : Greater than N/E: Not established